



### **CHAMELEON**


The new Chameleon family of 100mm downlights by BOLD Lighting will transform your perspective on how light is specified and experienced in an ever-changing world.

Chameleon downlights offer a unique interchangeability of optics, accessories, trims, and reflectors which can be easily modified at any point in the design process, including after the fixture has been installed. As an added feature, the adjustable luminaire comes standard with a zoomable lens, giving specifiers even more flexibility to transform a changing environment.

Chameleon is available in fixed, wallwash, and adjustable luminaires with a wide range of lumen outputs, optics, trims and finishes to blend in with any environment ... **transformed** to transform.







### **Adaptable Flexibility**

Has the client changed their mind? Have the finishes been revised at the last moment? Did the artwork get smaller?

Don't worry! The Chameleon family has been designed specifically so designers can expect the unexpected.

Chameleon's interchangeable components can quickly be modified when the environment unexpectedly changes, even after the fixture has been installed.

Whether you need to change from trim to trimless; round to square; white to pink;  $15^{\circ}$  to  $50^{\circ}$ , Chameleon gives you the flexibility to blend in with whatever the space demands.

### **Endless Possibilities**

With performance in mind, the Chameleon family offers fixed, adjustable, and wallwash luminaires with multiple power outputs, optics, and dimming capabilities.

Our downlights easily integrate into a luxury hotel lobby, office atrium, intimate restaurant, or any other space where specific performance factors are required.

With an expansive offering of options, the Chameleon family is your one stop source for all downlighting applications.


## THE FIXED ACCENT




























### The Finishing Touch

Chameleon offers a wide variety of trim shapes, shades and optical accessories for a high-quality finish.





WF - Flat White



BF - Flat Black



BG - Bright Gold



BC - Bright Copper




DC -Diffuse Chrome



DG - Diffuse Gold





### 3

### **Bold Performance**


Chameleon range provide bold performance and efficacy (up to 2,500 lm delivered at 26W); with long-term energy and maintenance savings; high-output capabilities; and exceptional color rendering and consistency (within a 2-step MacAdam ellipse).

- □ Up to 2,500lm delivered output
- □ Trim, trimless and millwork mounting options
- ☐ High CRI, up to +97 CRI, available upon request
- □ Dim-to-Warm capability 3000K to 1800K
- □ Tunable white capability 2700K to 5000K
- Wide range of optical options
- 5 years limited warranty
- Wide range of trims and reflectors finishes

A vibrant color palette of anti-glare trim to add a touch to your space design. Our downlights can morph on demand.

Accessories are interchangeable even after installation.

When projects conditions suddenly change, you can instantly adapt.



### **Ingenuity from Inside**

### **Compact but powerful**

Our heatsink is more efficient than ever. Specially designed optics significantly Not only have we been able to increase reduce glare and offer a maximized the luminous output of the fixtures, but visual comfort with deep regressed we have also extended their lifetime in light sources and anti-glare accessories the process.

### **Unbeatable color**

We use only the highest quality LED light 
The finishing touch sources, providing color consistency A wide variety of trim shapes, colors within a 2-step MacAdam ellipse and a and optical accessories for a highflawless color rendering.

### **Cutting-edge optics**

Our in-house, designed optics direct light precisely where it is needed with a clean beam.

### **Glare control**


(solite lenses, honeycomb louvers and cross baffle louvers).

quality finish.


### **Designed to Transform**


To offer even more design freedom and flexibility to architects, interior and lighting designers, a wide range of optical accessories is available to convert the light effect to the specific needs of the scene.

Each downlight can take up to 3 optical devices at the same time (snoot, honeycomb louvers, cross baffle louver and optical various beam shaping lens).



### Quietly **Adjustable**





### See light in different angles

Our adjustable downlight offers a great unique feature. A zoomable lens allowing lighting designers, architects and interior designers to use a single optic with a flexibility of light distribution from 10° to 50° beam angles thus pushing the limits of performance further.







Spec-grade performance LED downlights. Optimal for hospitality, commercial, high-end residential and corporate projects.

The Chameleon R4 / S4 downlights offer a high output, presice optics, a wide range of mounting options, reflector finishes, and optical accessories.

- ─ Up to 2,500lm delivered output
- Trim, trimless and millwork mounting options
- ☐ High CRI, up to +97 CRI, available upon request
- Dim-to-Warm capability 3000K to 1800K
- ☐ Tunable White capability 2700K to 5000K
- ─ Wide Range of optical options
- 5 years limited warranty
- Wide range of trims and reflectors finishes




**C**hameleon


R4"/S4" QUIETLY FIXED

### Code example:


**C4-F**R1W-L10R-WW-S827-9-0 **C4-F**S1W-L10R-WW-S827-9-0


| Series | Mounting |                           | Tri | m Color |   | Output <sup>1</sup> |    | Voltage                   | Control |                      |
|--------|----------|---------------------------|-----|---------|---|---------------------|----|---------------------------|---------|----------------------|
| C4-F   | R1<br>S1 | Round/Square<br>Trim      | w   | White   | L | 10W (1108lm)        | 1  | 120V                      | 0       | Non-Dim              |
|        | RO<br>SO | Round/Square<br>Trimless  | В   | Black   | М | 12W (1345lm)        | U² | Universal<br>120V to 277V | 1       | 0-10 to 1%           |
|        | R2<br>S2 | Round/Square<br>Trim with | s   | Grey    | н | 18W (1681lm)        |    |                           | 2       | 0-10<br>fade-off     |
|        |          | Constant Force<br>Spring  | х   | Custom  | ٧ | 22W (2686lm)        |    |                           | D       | Dali                 |
|        | R3<br>S3 | Round/Square<br>Millwork  |     |         |   |                     |    |                           | P       | Phase ELV<br>& Triac |
|        |          |                           |     |         |   |                     |    |                           | L       | Lutron               |
|        |          |                           |     |         |   |                     |    |                           | x       | DMX                  |





FRONT VIEW





| F  | Housing  |   | Ref. Color      |   | IP Rating |   | Optics Type |   | LED CRI |     | LED CCT       |   | Emergency |                | Accessories     |  |
|----|----------|---|-----------------|---|-----------|---|-------------|---|---------|-----|---------------|---|-----------|----------------|-----------------|--|
| R  | Remodel  | w | Flat White      | D | Dry       | s | 12°         | 8 | 80      | 27  | 2700K         | N | No        | 0              | No Accessories  |  |
| N  | Non-IC   | В | Flat Black      | w | Wet       | м | 24°         | 9 | 90      | 30  | 3000K         | 9 | 90 mins   | С              | Clear Lens      |  |
| 13 | IC       | N | Black Nickel    |   |           | F | 36°         | Т | Thrive  | 35  | 3500K         |   |           | D <sub>e</sub> | Diffuse lens    |  |
| A³ | Airtight | с | Specular Chrome |   |           |   |             |   |         | 40  | 4000K         |   |           | E7             | Elliptical Lens |  |
|    |          | D | Diffuse Chrome  |   |           |   |             |   |         | WD⁴ | 3000K - 1800K |   |           | н              | Honeycomb Lens  |  |
|    |          | G | Bright Gold     |   |           |   |             |   |         | TW⁵ | 2700K - 5000K |   |           | s              | Solite Lens     |  |
|    |          | E | Diffuse Gold    |   |           |   |             |   |         | СС  | RGBW          |   |           |                |                 |  |
|    |          | x | Custom          |   |           |   |             |   |         |     |               |   |           |                |                 |  |

### Notes:

- <sup>1</sup> Denotes output at 3000K CRI 80,

- Denotes output at 3000K CRI 80, unless otherwise noted.

  Not applicable for ELV dimming.


  Chicago Plenum rated.


  Dim-1o-Warm only available in CRI +90.

  Tunable White available in 0-10V, DMX and DALL.

- I Unable White available in 0-DMX and DALI.
   Diffuse lenses available in different angles.
   Elliptical lenses available in different angles.

Consult factory for lead-times. Bold Lighting reserves the right to make technical changes without notice.







The **adjustable** accent



Spec-grade performance LED downlights. Optimal for hospitality, commercial, high-end residential and corporate projects. The Chameleon R4 / S4 downlights offer a high output, presice optics, a

wide range of mounting options, reflector finishes, and optical accessories.


- □ Up to 2,500lm delivered output
- ☐ Trim, trimless and millwork mounting options
- ☐ High CRI, up to +97 CRI, available upon request
- Dim-to-Warm capability 3000K to 1800K
- ☐ Tunable White capability 2700K to 5000K
- Gear driven tilt 0° to 35° and 360° lockable rotation
- 5 years limited warranty
- Wide range of trims and reflectors finishes



### Code example:

C4-ARIW-L10R-WW-S827-9-0 **C4-A**S1W-L10R-WW-S827-9-0

| Series |                            | Mounting  | Tri    | m Color        |        | Output <sup>1</sup>          |    | Voltage                   | Control |                                |  |
|--------|----------------------------|---|--------|----------------|--------|------------------------------|----|---------------------------|---------|--------------------------------|--|
| C4-A   | R1 Round/Square<br>S1 Trim |   | w      | White          | L      | 10W (1108lm)                 | 1  | 120V                      | 0       | Non-Dim                        |  |
|        | RO<br>SO                   | Round/Square<br>Trimless                              | В      | Black          | М      | 12W (1345lm)                 | U² | Universal<br>120V to 277V | 1       | 0-10 to 1%                     |  |
|        | R2<br>S2                   | Round/Square<br>Trim with<br>Constant Force<br>Spring | s<br>x | Grey<br>Custom | H<br>V | 18W (1681lm)<br>22W (2749lm) |    |                           | 2<br>D  | 0-10<br>fade-off<br>Dali       |  |
|        | R3<br>S3                   | Round/Square<br>Millwork                              |        |                |        |                              |    |                           | P<br>L  | Phase ELV<br>& Triac<br>Lutron |  |
|        |                            |   |        |                |        |                              |    |                           | x       | DMX                            |  |



| H              | lousing  |   | Ref. Color      | IP Ro | ating | Optio | cs Type | LE | D CRI  |                 | LED CCT       |   | Emergency |                | Accessories     |
|----------------|----------|---|-----------------|-------|-------|-------|---------|----|--------|-----------------|---------------|---|-----------|----------------|-----------------|
| R              | Remodel  | w | Flat White      | D     | Dry   | s     | 12°     | 8  | 80     | 27              | 2700K         | N | No        | 0              | No Accessories  |
| N              | Non-IC   | В | Flat Black      | w     | Wet   | м     | 24°     | 9  | 90     | 30              | 3000K         | 9 | 90 mins   | С              | Clear Lens      |
| 13             | IC       | N | Black Nickel    |       |       | F     | 45°     | т  | Thrive | 35              | 3500K         |   |           | D <sub>6</sub> | Diffuse lens    |
| A <sup>3</sup> | Airtight | С | Specular Chrome |       |       |       |         |    |        | 40              | 4000K         |   |           | E <sup>7</sup> | Elliptical Lens |
|                |          | D | Diffuse Chrome  |       |       |       |         |    |        | WD⁴             | 3000K - 1800K |   |           | н              | Honeycomb Lens  |
|                |          | G | Bright Gold     |       |       |       |         |    |        | TW <sup>5</sup> | 2700K - 5000K |   |           | s              | Solite Lens     |
|                |          | E | Diffuse Gold    |       |       |       |         |    |        | СС              | RGBW          |   |           |                |                 |
|                |          | x | Custom          |       |       |       |         |    |        |                 |               |   |           |                |                 |



- <sup>1</sup> Denotes output at 3000K CRI 80,

- Denotes output a 3000x Cat 80, unless otherwise noted.

  Not applicable for ELV dimming.

  Chicago Plenum rated.

  Dim-1o-Warm only available in CRI +90.


  Tunable White available in 0-10V,


- DMX and DALI.


  Diffuse lenses available in different angles.

  Elliptical lenses available in different angles.

Consult factory for lead-times. Bold Lighting reserves the right to make technical changes without notice.







Spec-grade performance LED downlights. Optimal for hospitality,

- ─ Up to 2,500lm delivered output
- Trim, trimless and millwork mounting options
- ☐ High CRI, up to +97 CRI, available upon request
- Dim-to-Warm capability 3000K to 1800K
- ☐ Tunable White capability 2700K to 5000K
- ☐ High uniformity light distribution Emin./ Emax.= 1/3
- 5 years limited warranty
- Wide range of trims and reflectors finishes




**C**hameleon


R4"/S4" QUIETLY WASHED

### Code example:


**C4-W** R1W-L10 R-WW-M827-9-0 **C4-W**S1W-L10R-WW-M827-9-0


| Series | eries Mounting |   | Trin   | n Color        |        | Output <sup>1</sup>          |    | Voltage                   | Control |                          |  |
|--------|----------------|---|--------|----------------|--------|------------------------------|----|---------------------------|---------|--------------------------|--|
| C4-W   | R1<br>S1       | Round/Square<br>Trim                                  | w      | White          | L      | 10W (1108lm)                 | 1  | 120V                      | 0       | Non-Dim                  |  |
|        | R0<br>S0       | Round/Square<br>Trimless                              | В      | Black          | М      | 12W (1345lm)                 | U² | Universal<br>120V to 277V | 1       | 0-10 to 1%               |  |
|        | R2<br>S2       | Round/Square<br>Trim with<br>Constant Force<br>Spring | s<br>x | Grey<br>Custom | H<br>V | 18W (1681lm)<br>22W (1718lm) |    |                           | 2<br>D  | 0-10<br>fade-off<br>Dali |  |
|        | R3<br>S3       | Round/Square<br>Millwork                              |        |                |        |                              |    |                           | P       | Phase ELV<br>& Triac     |  |
|        |                |   |        |                |        |                              |    |                           | L       | Lutron                   |  |
|        |                |   |        |                |        |                              |    |                           | x       | DMX                      |  |





FRONT VIEW





|    | Housing  |   | Ref. Color      | IP R | ating | Opt | ics Type | LE | D CRI  |                 | LED CCT       | Em | ergency |   | Accessories    |
|----|----------|---|-----------------|------|-------|-----|----------|----|--------|-----------------|---------------|----|---------|---|----------------|
| R  | Remodel  | w | Flat White      | D    | Dry   | м   | 24°      | 8  | 80     | 27              | 2700K         | N  | No      | 0 | No Accessories |
| N  | Non-IC   | В | Flat Black      | w    | Wet   |     |          | 9  | 90     | 30              | 3000K         | 9  | 90 mins |   |                |
| 13 | IC       | N | Black Nickel    |      |       |     |          | т  | Thrive | 35              | 3500K         |    |         |   |                |
| A  | Airtight | С | Specular Chrome |      |       |     |          |    |        | 40              | 4000K         |    |         |   |                |
|    |          | D | Diffuse Chrome  |      |       |     |          |    |        | WD⁴             | 3000K - 1800K |    |         |   |                |
|    |          | G | Bright Gold     |      |       |     |          |    |        | TW <sup>5</sup> | 2700K - 5000K |    |         |   |                |
|    |          | E | Diffuse Gold    |      |       |     |          |    |        | СС              | RGBW          |    |         |   |                |
|    |          | x | Custom          |      |       |     |          |    |        |                 |               |    |         |   |                |

### Notes:


- <sup>1</sup> Denotes output at 3000K CRI 80,
- unless otherwise noted.

  Not applicable for ELV dimming.
- 3 Chicago Plenum rated. 4 Dim-to-Warm only available in
- CRI +90.

  Tunable White available in 0-10V,
  DMX and DALI.
- Consult factory for lead-times. Bold Lighting reserves the right to make technical changes without notice.

### Chameleon

The washed accent







The **zoomable** accent



Spec-grade performance LED downlights. Optimal for hospitality, commercial, high-end residential and corporate projects.

The Chameleon R4 / S4 downlights offer a high output, presice optics, a wide range of mounting options, reflector finishes, and optical accessories.


- ─ Up to 2,500lm delivered output
- Trim, trimless and millwork mounting options
- ☐ High CRI, up to +97 CRI, available upon request
- Dim-to-Warm capability 3000K to 1800K
- ☐ Tunable White capability 2700K to 5000K
- Gear driven tilt 0° to 35° and 360° lockable rotation
- ☐ Zoomable Lens from 10° to 50°
- 5 years limited warranty
- Wide range of trims and reflectors finishes



### Code example:

**C4-Z**R1W-L10R-WW-Z827-9-0 **C4-Z**S1W-L10R-WW-Z827-9-0

| Series | Series Mounting            |   | Tri    | m Color        |        | Output <sup>1</sup>          |    | Voltage                   | (      | Control                        |
|--------|----------------------------|---|--------|----------------|--------|------------------------------|----|---------------------------|--------|--------------------------------|
| C4-Z   | R1 Round/Square<br>S1 Trim |   | w      | White          | L      | 10W (1108lm)                 | 1  | 120V                      | 0      | Non-Dim                        |
|        | RO<br>SO                   | Round/Square<br>Trimless                              | В      | Black          | М      | 12W (1345lm)                 | U² | Universal<br>120V to 277V | 1      | 0-10 to 1%                     |
|        | R2<br>S2                   | Round/Square<br>Trim with<br>Constant Force<br>Spring | s<br>x | Grey<br>Custom | H<br>V | 18W (1681lm)<br>22W (2343lm) |    |                           | 2<br>D | 0-10<br>fade-off<br>Dali       |
|        | R3<br>S3                   | Round/Square<br>Millwork                              |        |                |        |                              |    |                           | P<br>L | Phase ELV<br>& Triac<br>Lutron |
|        |                            |   |        |                |        |                              |    |                           | x      | DMX                            |



TOP VIEW

|   | Н          | ousing   |   | Ref. Color      | IP Ro | ating | Op | otics Type | LE | D CRI  |                 | LED CCT       | Em | ergency |                | Accessories     |
|---|------------|----------|---|-----------------|-------|-------|----|------------|----|--------|-----------------|---------------|----|---------|----------------|-----------------|
|   | ₹          | Remodel  | w | Flat White      | D     | Dry   | z  | 10°-50°    | 8  | 80     | 27              | 2700K         | N  | No      | o              | No Accessories  |
| ı | ١          | Non-IC   | В | Flat Black      | w     | Wet   |    |            | 9  | 90     | 30              | 3000K         | 9  | 90 mins | С              | Clear Lens      |
| ı | 3          | IC       | N | Black Nickel    |       |       |    |            | T  | Thrive | 35              | 3500K         |    |         | D <sub>6</sub> | Diffuse lens    |
| 1 | <b>\</b> 3 | Airtight | С | Specular Chrome |       |       |    |            |    |        | 40              | 4000K         |    |         | E <sup>7</sup> | Elliptical Lens |
|   |            |          | D | Diffuse Chrome  |       |       |    |            |    |        | WD⁴             | 3000K - 1800K |    |         | н              | Honeycomb Lens  |
|   |            |          | G | Bright Gold     |       |       |    |            |    |        | TW <sup>5</sup> | 2700K - 5000K |    |         | s              | Solite Lens     |
|   |            |          | E | Diffuse Gold    |       |       |    |            |    |        |                 |               |    |         |                |                 |
|   |            |          | x | Custom          |       |       |    |            |    |        |                 |               |    |         |                |                 |



<sup>1</sup> Denotes output at 3000K CRI 80,

FRONT VIEW

- Denotes output a 3000x Cat 80, unless otherwise noted.

  Not applicable for ELV dimming.

  Chicago Plenum rated.

  Dim-1o-Warm only available in CRI +90.

  Tunable White available in 0-10V,

- DMX and DALI.
   Diffuse lenses available in different angles.
   Elliptical lenses available in different angles.
   It different angles.

Consult factory for lead-times. Bold Lighting reserves the right to make technical changes without notice.




R4"/S4" Photometric data: Type C Polar Curves

# Narrow Distribution 12° Medium Distribution 24° Max. 7,550cd Notes: Other beam distribution available on demand.

1,000lm

Please consult factory.




## Wallwash Distribution Wallwasher optimal spacing Wallwasher optimal spacing Plan View SET BACK X= WALL HEIGHT ASPACING Y= 1.4 X SPACING Y= 1.4 X

### How **Chameleon** integrates

Hospitality. Corporate projects. Commercial. Retail. Residential. Different worlds but yet so close when it comes to lighting quality needs.

Be it to highlight beauty, to attract people, to create an atmosphere or to emphasize details, Chameleon is the ultimate solution for special high ceiling requirements that allows you to light any possible setting.



Max. 2,720cd











### QUIETLY

Atlanta, Georgia - USA +1 678-903-4061

www.boldlighting.com