SNOOT

PENDANT





Our Magnetic track system, SPECTER, is a highly configurable, 2 circuits, 24VDC low voltage track system. Thanks to its magnet mounting technology, the modules are inter-changeable instantaneously. Our track is available in ceiling pendant, surface and recessed mounting for both ceiling and walls. SPECTER track is also available with an optional linear uplight feature.

The snoot pendant module complements the SPECTER range with a minimalistic pendant cylinder equipped with a wide range of optics and optical accessories allowing professional lighting.

- Up to 1,300lm delivered output
- Available in 2 diameter sizes, 1.25" and 2"
- Various optical accessories available such as beam shaping lenses, Honeycomb louvers or barndoors
- Beam options, narrow, medium, Flood and wide
- Fixtures designed to mount in SPECTER track
- Available in 4 standard finishes: Black, white, silver and bronze

Notes: Track available in 0-10V, ELV and DALI dimming

Code example:

SNP-1-927-M-BL

Delivered Lumen Output

	Size / Output*		CRI		CCT.		Beam		Finish	
1	Diameter 1.5"	740lm (8W)	8	+80	27	2700K	N	12°	WH	Flat White
2	Diameter 2"	1230lm (15W)	9	+90	30	3000K	M	24°	BL	Flat Black
					35	3500K	F	36°	SL	Silver
					40	4000K	W	50°	BZ	Bronze

Standard Finishes



LABELS:



ETL tested to UL standards 2108, Dry Location



CE Certified

Size Watts CRI +80 CRI +90 2700K 3000K 4000K 2700K 3000K 4000K 8W 670lm 744lm 876lm 630lm 700lm 824lm 15W 1100lm 1222lm 1438lm 1040lm 1156lm 1359lm



PENDANT



Photometric data: Type C Polar Curves



